



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :

G01S 5/06, H04Q 7/38

A1

(11) International Publication Number:

WO 98/48294

(43) International Publication Date:

29 October 1998 (29.10.98)

(21) International Application Number: PCT/US98/06276

(22) International Filing Date: 2 April 1998 (02.04.98)

(30) Priority Data:

08/838,027

22 April 1997 (22.04.97)

US

(71) Applicant: ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).

(72) Inventors: IRVIN, David, R.; 3101 Churchill Road, Raleigh, NC 27607 (US). RAMESH, Rajaram; 403 Dantan Drive, Cary, NC 27511 (US). MOLNAR, Karl; 110 Flying Leaf Court, Cary, NC 27513 (US).


(74) Agents: GRUDZIECKI, Ronald, L. et al.; Burns, Doane, Swecker & Mathis, L.L.P., P.O. Box 1404, Alexandria, VA 22313-1404 (US).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: A CELLULAR POSITIONING SYSTEM THAT COMPENSATES FOR RECEIVED SIGNAL DELAYS IN POSITIONING RADIO RECEIVERS



(57) Abstract

A positioning system locates a mobile unit by compensating for component tolerances in time-of-arrivals of received signals at a plurality of positioning radio receivers. The system determines detection times of the received radio signals at the positioning radio receivers. The system takes into account pre-stored signal delays associated with one or more receiver stages of the corresponding positioning radio receivers and the detection times, for determining time-of-arrivals for the received radio signals.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A CELLULAR POSITIONING SYSTEM THAT COMPENSATES FOR RECEIVED
SIGNAL DELAYS IN POSITIONING RADIO RECEIVERS

BACKGROUND

5 This invention generally relates to the field of
communication systems and, more particularly, to
compensating for received signal delays in positioning radio
receivers.

 The growth of commercial radiocommunications and,
10 in particular, the explosive growth of cellular
radiotelephone systems have changed the ways in which people
communicate. One survey indicates that about 80% of the
people who purchase mobile communication units and service
subscriptions do so to enhance their personal security.
15 Presumably, many of these subscribers would expect to use
their mobile units to aid them in urgent situations, e.g.,
when their vehicle has become disabled or in an emergency
situation requiring rapid medical and/or police response.
In these circumstances it would be desirable that the
20 radiocommunication system be able to determine a location of
the mobile unit, particularly in the case where the
subscriber does not know his or her precise location.
Moreover, it is expected that the FCC will soon require that
network operators forward the position of an emergency
25 caller to the emergency service provider.

 There are many techniques available to generate
mobile unit position information. In one positioning
system, the mobile unit could estimate its own position and
send a message with its coordinates when placing an
30 emergency call. This could be accomplished by, for example,

providing the mobile unit with a Global positioning System (GPS) receiver that receives location information from the GPS satellite network. The mobile unit can then transmit this information to the system, which would then forward it to the emergency service provider. This requires, however, significant modification of existing mobile units to include GPS receivers, as well as additional signalling between the mobile units and base stations.

Alternatively, the base stations which transmit signals to, and receive signals from, the mobile units could be used to determine the mobile unit's location. Various techniques, including attenuation of a mobile unit's signal, angle-of-arrival, and difference between the time-of-arrival (TDOA) of a mobile unit's signal at different base stations, have been suggested for usage in providing mobile unit location information. See, for example, the article entitled "Time Difference of Arrival Technology for Locating Narrowband Cellular Signals" by Louis A. Stilp, SPIE Vol. 2602, pp. 134-144. Another system used for locating mobile units in radiocommunication systems is an adjunct system that operates independent of the radiocommunication system. The adjunct system includes its own base stations for locating the mobile unit. The adjunct system may, however, share various components (e.g., an antenna) with the radiocommunication system but processes signals separately. This may be advantageous, for example, as an expedient solution to providing mobile unit location without modifying the large number of existing base stations in a system.

For determining the position of a target mobile unit, some positioning algorithms rely on received signal

time-of-arrivals reported from three positioning radio receivers at three or more locations. By processing the time-of-arrivals, the position of the target mobile unit is determined by way of a known constant-radius-circle position-determination algorithm. This algorithm relies on the point of intersection of at least three circles with radiuses corresponding to the time-of-arrivals reported from the positioning receivers.

In practice, a positioning radio receiver, however determines a detection time corresponding to the time when the received signal from the target mobile unit is detected, rather than the time when the received signal actually arrives at the positioning radio receiver. The detection time is the time at which the received signal emerges from the receiver's detector, having made its way through the receiver's various RF and IF stages, which add signal delays to the detection of the received signal. Under ideal conditions, the distinction between detection time and arrival time would be insignificant. Because each receiver in a given positioning system would introduce the same amount of delay, which could be readily removed by the system's position-determination algorithm. Due to component tolerances, however, the assumption that the various positioning receivers will have equal delay is not valid.

For example, certain kinds of IF filters vary greatly in group delay -- the time required to propagate energy through the filter -- even for nominally identical components. Empirical data suggest that ceramic IF filters, which are widely used in receivers because of their favorable cost/performance characteristics, show group-delay

variations of about plus-or-minus 100 nanoseconds from mean. As a result, the determination of position is subject to various uncertainties and tolerances, which result in position inaccuracy and ambiguity. In a positioning system otherwise under ideal conditions, a 100-nanosecond uncertainty in time-of-arrival of the received signal introduces a positional uncertainty of about 30 meters (about 100 feet). Referring to FIG. 1, the position uncertainty caused by plus-or-minus 100 nano second is shown by hashed lines between the crossings of the circles corresponding to time of arrivals of a first positioning radio receiver and a second positioning radio receiver that are used for determining the position of the mobile unit. Each positioning radio receiver is represented by two co-centric circles with radiuses showing the plus-of-minus 100 nano second uncertainty. Thus, positioning radio receivers that have components, e.g., IF filters, drawn from the extremes of tolerance distributions subject a system to positioning errors and ambiguities on the order of several hundred feet. Therefore, there exists a need for a positioning system that compensates for positional uncertainty introduced by component tolerances in positioning radio receivers.

25

SUMMARY

The present invention that addresses this need is exemplified in a positioning system that improves positioning accuracy by measuring and pre-storing signal delays associated with positioning radio receivers. Accordingly, the positioning system for locating the mobile

30

unit according to the present invention includes a detector that detects a received radio signal from the mobile unit by a corresponding positioning radio receiver, and a timing device that determines a detection time associated with the received signal. A processor determines a time-of-arrival for the received radio signal based on the detection time and a measured or computed signal delay that is pre-stored in a storage device. A mobile unit locator processes time-of-arrivals from a plurality of positioning radio receiver to locate the mobile unit.

According to more detailed features of the invention, the signal delay includes a measured or computed group delay associated with a filter included in one of the receiver stages and a measured or computed transmission-line delay associated with a transmission line included in radio receiver. Preferably, the time-of-arrival is based on the difference between the signal delay and the detection time. In an exemplary embodiment, however, the time-of-arrival may be based on the detection time and a delta value derived from the difference of the signal delay relative to a nominal value.

Other features and advantages of the present invention will become apparent from the following description of the preferred embodiment, taken in conjunction with the accompanying drawings, which illustrate, by way of example, the principles of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing positional inaccuracies associated with positioning a mobile unit using a conventional positioning radio receiver.

5 FIG. 2 is a block diagram of a positioning system that advantageously incorporates the present invention.

FIG. 3 is a block diagram of a positioning radio receiver used in the system of FIG. 2.

10 FIG. 4 is a diagram of a delay message used for transmitting a signal delay associated with the receiver of FIG. 3.

DETAILED DESCRIPTION

Referring to FIG. 1, a positioning system 1 that
15 advantageously incorporates the present invention is shown. In an exemplary embodiment, the positioning system 1 is an adjunct positioning system similar to the one disclosed in U.S. Patent No. 5,327,144 to Stilp et al., entitled
"Cellular Telephone Location System", the disclosure of
20 which is incorporated here by reference. As it will become apparent later in the disclosure, in addition to adjunct positioning systems, non-adjunct positioning systems could equally take advantage of the present invention. The positioning system 1 includes three positioning radio
25 receivers 2, 3, 4 that are not necessary co-located with the base stations of a cellular radiocommunication system within which a plurality of subscriber mobile units operates. Also shown is a cellular system base station 5 that supports radiocommunication within a cell 6 and, in particular with a
30 mobile unit 7 whose location is to be determined according

to the present invention. The positioning radio receivers 2, 3 and 4 monitor accesses to the system by the mobile unit 7. When the mobile unit 7 makes an emergency access, the positioning system 1 processes time-of-arrivals of signals received from the mobile unit 7 at the positioning receivers 2, 3 and 4 to determine the position of mobile unit 7 using, for example, the well known constant-radius-circle position-determination algorithm. In an exemplary embodiment, the processing of the time-of-arrivals from the positioning radio receiver 2, 3, 4 takes place in a central station 8 that reports the position information of the mobile unit 7 to an emergency service center 9.

According to the present invention, a measured or computed signal delay associated with one or more receiver stages of the positioning radio receivers 2, 3, 4 is pre-stored either in each one of the positioning radio receivers or in the central station 8. When determining the position of the mobile unit 7, a mobile unit position locator 5 incorporated in the central station 8 processes time-of-arrivals that are derived based on the signal delays of corresponding positioning radio receivers. Therefore, unlike conventional methods, the present invention takes into account pre-stored variations of signal delays associated with the positioning radio receivers when making positioning determination. By measuring and pre-storing the signal delays, the positioning system of the invention can accurately locate the mobile unit 7 without introducing uncertainties associated with component tolerances of the positioning radio receivers 2, 3, 4.

Referring to FIG. 3, a block diagram of one positioning radio receiver 10 of the positioning system is shown. The positioning radio receiver 10 includes a plurality of receiver stages each of which may introduce a measurable signal delays to the detection of the received signal. As shown, a receiver antenna 11 receives a transmitted signal from the mobile unit 7 (shown in FIG. 2) and applies it to an RF stage 12 through a transmission line 14. It is well known that the transmission line 14 connecting the antenna 11 to the RF stage 12 delays the received signal by a transmission-line delay. The RF stage 12, which provides pre-amplification and receiver selectivity, applies the received signal to an IF stage 16 for down conversion in a well known manner. The IF stage 16 provides an IF signal on line 18 that contains the information carried by the received signal. In order to provide the IF signal, the IF stage 16 uses an IF filter 20, for example, a ceramic filter, which introduces an additional group-delay. Therefore, the signal delay of the received signal includes both the transmission-line delay and the group-delay. The IF signal is applied to a detector 22 that detects the received signal at a detection time. The positioning radio receivers measures the detection time using a well known logic circuit 24 and timing device, such as a clock device 26.

In the present invention, the transmission-line delay and the group-delay are measured or computed according to well known methods that determine signal delay associated with RF stages of a received signal. For example, the signal delay for each positioning radio receiver 2, 3, 4 may

be measured at time of manufacture or time of installation by a technician that uses a dual-trace oscilloscope or automated means. The transmission line delay may be measured or computed based on line length and velocity factor. The value of the signal delay, which is usually in nanoseconds range, is pre-stored in a signal delay storage device 28, preferably as a binary coded decimal number. The storage device may 28 represents the pre-stored binary coded decimal number by means of a DIP switch or by means of binary bytes or words stored in a non-volatile memory device.

In one exemplary embodiment of the invention, the positioning radio receiver 10 subtracts, using a subtractor 30, the pre-stored signal delay from the detection time to determine the actual time-of-arrival of the received signal. Under this arrangement, the positioning radio receiver 10 reports the time-of-arrival time to the central station 8 for processing with other time-of-arrivals received from other similar positioning radio receivers. The positioning radio receiver reports the time-of-arrival by means of a transmitter 32 that is linked to the central controller through either a wired or a wireless transmission medium.

According to one variation of the invention, the positioning radio receiver 10 sends the signal delay to the central station 8 along with the detection time. For example, in one variation, the positioning radio receiver 10 transmits to the central station 8 a digitally encoded delay message having two fields. As shown in FIG. 4, a first field 34 conveys the detection time, and a second field 36 conveys the receiver's signal delay. In another variation,

the second field 36 may contain a delta value corresponding to the difference between the signal delay relative to a nominal value. Under this arrangement, the central station 8 is responsible for subtracting the signal delay from the
5 detection time to determine the time-of-arrival. The positioning radio receiver 10 may convey the delay message to the central station 8 occasionally or periodically in order to provide updated position information. Under this arrangement, the central station 8, which may store the
10 transmitted delay messages, would subtract the pre-stored signal delay from the periodically updated detection times for determining the time-of-arrivals on a continuous basis.

Referring back to FIG. 2, according to another
15 aspect of the present invention, the central station 8 includes a central storage device 38 for storing the signal delay associated with each one of the positioning radio receivers. According to this aspect of the invention, the signal delay is determined at time of system installation
20 using a reference signal source at a known location that is, preferably, equidistant from each of the positioning receivers. By determining the time-of-arrivals from the reference signal source, the signal delay associated with each one of the positioning radio receivers may be measured.
25 The signal delays of the radio positioning receivers 2, 3 and 4 may be stored in the central storage device 38. The stored signal delays may then be retrieved by the mobile position locator 15, which also receives the detection times transmitted from the positioning radio receivers 2, 3, 4

during the processing of the time-of-arrivals, for locating the mobile unit 7.

From the foregoing description it would be appreciated that the present invention introduces accuracy
5 into positioning algorithms that use time-of-arrivals for locating mobile units by removing tolerance variations associated with the components used in the positioning radio receivers. In this way, the present invention can be used in any communication system, adjunct or non-adjunct, to
10 accurately locate a mobile unit.

Although the invention has been described in detail with reference only to the presently preferred embodiment, those skilled in the art will appreciate that various modifications can be made without departing from the
15 invention. Accordingly, the invention is defined only by the following claims which are intended to embrace all equivalents thereof.

What is claimed is:

1. An apparatus for locating a mobile unit using a plurality of positioning radio receivers, comprising:
 - 5 a detector that detects a received radio signal from the mobile unit at a corresponding positioning radio receivers;
 - a timing device that determines a detection time associated with the received signal;
 - 10 a storage device that stores a signal delay associated with one or more receiver stages of the corresponding positioning radio receiver; and
 - a processor that determines a time-of-arrival for the received radio signal based on the detection time
 - 15 and the signal delay, and
 - a mobile unit locator that processes time-of-arrivals at the plurality of positioning radio receiver to determine the position of the mobile unit.
- 20 2. The apparatus of claim 1, wherein the signal delay corresponds to a group delay associated with a filter included in one of the receiver stages.
3. The apparatus of claim 1, wherein the signal
- 25 delay corresponds to a transmission-line delay.
4. The apparatus of claim 1, wherein the time-of-arrival is based on the difference between the signal delay and the detection time.

5. The apparatus of claim 1, wherein the time-of-arrival is based on the detection time and a delta value derived from the difference of the signal delay relay to a nominal value.

5

6. The apparatus of claim 1, wherein the signal delay is determined using a reference signal source at a known location that is equidistant from each of the positioning receivers.

10

7. A positioning radio receiver, comprising:
one or more receiver stages that process a received radio signal;
a storage device that pre-stores a signal
15 delay associated with the one or more receiver stages;
a detector that produces a detection time corresponding to a time when the received radio signal is detected by one of the receiver stages; and
a transmitter for transmitting time of
20 arrival information based on the detection time and the signal delay.

8. The radio receiver of claim 7, wherein one of the receiver stages includes a filter, and wherein the
25 signal delay corresponds to a group delay associated with the filter.

9. The radio receiver of claim 7, wherein the receiver includes a transmission line, and wherein the

14

signal delay corresponds to a transmission-line delay associated with the transmission line.

10. The radio receiver of claim 7, wherein the
5 transmitter transmits the time-of-arrival information device based on the difference between the signal delay and the detection time.

11. The radio receiver of claim 7, wherein
10 transmitter transmits the time-of-arrival information that include the signal delay and the detection time.

12. The radio receiver of claim 7, wherein the
time-of-arrival information is based on a delta value
15 derived from the difference of the signal delay to a nominal value.

13. The radio receiver of claim 7, wherein the
transmitter transmits time-of-arrival the information
20 periodically.

14. A method for positioning a mobile unit,
comprising:
detecting a received radio signal from the
25 mobile unit by at least one corresponding positioning radio receiver;
determining a detection time associated with
the received signal;

15

retrieving a pre-stored signal delay associated with one or more receiver stages of the corresponding positioning radio receiver; and

5 determining a time-of-arrival for the received radio signal based on the detection time and the pre-stored signal delay.

15. The method of claim 14 further including processing time-of-arrivals from a plurality of positioning
10 radio receiver to determine the position of the mobile unit.

16. The method of claim 14, wherein the signal delay corresponds to a group delay associated with a filter included in one of the receiver stages.
15

17. The method of claim 14, wherein the signal delay corresponds to a transmission-line delay associated with a transmission line included in the receiver.

20 18. The method of claim 14, wherein the time-of-arrival is based on the difference between the signal delay and the detection time.

19. The method of claim 14, wherein the time-of-
25 arrival is based on the detection time and a delta value derived from the difference of the signal delay relative to a nominal value.

20. A positioning system for locating a mobile
30 unit, comprising:

16

a plurality of positioning radio receivers
that each one includes:

one or more receiver stages that process a
received radio signal;

5 a detector that produces a detection time
corresponding to a time when the received radio signal is
detected by one of the receiver stages; and

a central station that includes:

a storage device that stores signal delays
10 associated with each one of the positioning radio receiver;
and

a mobile unit locator that processes
time-of-arrivals from the plurality of positioning radio
receivers to determine the position of the mobile unit,
15 wherein the time of arrivals are derived based on the
detection times from the positioning radio receives and the
signal delays.

21. The cellular positioning system of claim 20,
20 wherein the signal delays are pre-stored in the central
station.

22. The cellular positioning system of claim 20,
wherein the signal delays are transmitted from the
25 positioning radio receivers.

23. The cellular positioning system of claim 20,
wherein each one of the receivers includes a filter, and
wherein the signal delays corresponds to group delays
30 associated with the filters of the receivers.

24. The cellular positioning system of claim 20, wherein each one of the receivers includes a transmission line, and wherein the signal delays corresponds to transmission-line delays associated with the receivers.

5

25. The cellular positioning system of claim 20, wherein the time-of-arrivals are based on the differences between the signal delays and the detection time of the receivers.

10

26. The cellular positioning system of claim 20, wherein the signal delay is determined using a reference signal source at a known location that is equidistant from each of the positioning receivers.

15




FIG. 1




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/06276

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 G01S5/06 H04Q7/38

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04Q G01S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 144 315 A (SCHWAB CARL E ET AL) 1 September 1992 see column 5, line 31 - column 8, line 32; figures 1,5,6	1,7-10, 12-19
A	-----	11
X	US 5 058 200 A (HUANG CHIA-CHI ET AL) 15 October 1991 see column 5, line 13 - column 6, line 48 see column 7, line 3 - column 8, line 4; figures 3,4,8	1-6,20, 22-26
A	----- -/-	7,14

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

21 July 1998

Date of mailing of the international search report

31/07/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Van Dooren, G

INTERNATIONAL SEARCH REPORT

Inte. onal Application No

PCT/US 98/06276

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3 780 370 A (REEVES H) 18 December 1973 see column 2, line 29-57 see column 3, line 35-65; claims 1-3, 6-12, 17, 18, 29-31 see claims 34-37; figures 1, 6, 8	1-6, 20, 22-26
A	----- DE 40 05 368 A (ROHDE & SCHWARZ) 22 August 1991 see column 3, line 44 - column 4, line 46; figure 8	6, 7, 14, 21
X	----- STILP L A: "TIME DIFFERENCE OF ARRIVAL TECHNOLOGY FOR LOCATING NARROWBAND CELLULAR SIGNALS" WIRELESS TECHNOLOGIES AND SERVICES FOR CELLULAR AND PERSONAL COMMUNICATION SERVICES, vol. SPIE 2602, 25 October 1995 - 26 October 1996, PHILADELPHIA, USA, pages 134-144, XP002046631 cited in the application see page 140, line 20-36	1-3, 7-9, 14-17, 20-24
A	----- MOULY M ET AL: "THE PSEUDO-SYNCHRONISATION, A COSTLESS FEATURE TO OBTAIN THE GAINS OF A SYNCHRONISED CELLULAR NETWORK" MRC MOBILE RADIO CONFERENCE, 13 November 1991, pages 51-55, XP000618384	1, 7, 14, 20
A	----- SONG H -L: "AUTOMATIC VEHICLE LOCATION IN CELLULAR COMMUNICATIONS SYSTEMS" IEEE TRANSACTIONS ON VEHICULAR TECHNOLOGY, vol. 43, no. 4, 1 November 1994, pages 902-908, XP000493419	1, 7, 14, 20

INTERNATIONAL SEARCH REPORT

information on patent family members

Int. onal Application No

PCT/US 98/06276

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5144315 A	01-09-1992	AT 140799 T	15-08-1996
		CA 2009344 C	06-12-1994
		DE 69027872 D	29-08-1996
		DE 69027872 T	13-02-1997
		EP 0385600 A	05-09-1990
US 5058200 A	15-10-1991	CA 2042275 A	05-12-1991
US 3780370 A	18-12-1973	NONE	
DE 4005368 A	22-08-1991	DE 3841585 A	13-06-1990